

Sub  
B1

[illegible]

**ABSTRACT OF DISCLOSURE**

relates to a pyrotechnic device between two elements subjected to tensile and compressive forces. The device comprises at least one locking element along at least one of the elements in the locking direction. The device is released by the action of the pyrotechnic charge, which is characterised in that the locking element (21) is able to withstand the pressure of the gas produced by the pyrotechnic charge (23), the locking element (21) at its release does not require their return to the initial position.

safety systems for

**ABSTRACT OF DISCLOSURE**

relates to a pyrotechnic device between two elements subjected to tensile and compressive forces. The device comprises at least one locking element along at least one of the elements in the locking direction. The device is released by the action of the pyrotechnic charge, which is characterised in that the locking element (21) is able to withstand the pressure of the gas produced by the pyrotechnic charge (23), the locking element (21) at its release does not require their return to the initial position.

safety systems for

**ABSTRACT OF DISCLOSURE**

relates to a pyrotechnic device between two elements subjected to tensile and compressive forces. The device comprises at least one locking element along at least one of the elements in the locking direction. The device is released by the action of the pyrotechnic charge, which is characterised in that the locking element (21) is able to withstand the pressure of the gas produced by the pyrotechnic charge (23), the locking element (21) at its release does not require their return to the initial position.

safety systems for

**ABSTRACT OF DISCLOSURE**

relates to a pyrotechnic device between two elements subjected to tensile and compressive forces. The device comprises at least one locking element along at least one of the elements in the locking direction. The device is released by the action of the pyrotechnic charge, which is characterised in that the locking element (21) is able to withstand the pressure of the gas produced by the pyrotechnic charge (23), the locking element (21) at its release does not require their return to the initial position.

safety systems for